

## Product Selection Guide

Description	DIGI3UE	DigiTract 4	SAMOD II (Stand Alone)	GEN II-R	GEN II	ZonexCommander, ZonexCommander (Plus), ModCom II	RetroZone
<b>Number of Zones</b>	3	2 - 4	1	10	17	1 - 80	17-20
<b>Auto Changeover</b>	yes	yes	yes	yes	yes	yes	yes
<b>Capacity Control</b>	optional	yes	recom	yes	yes	yes	yes
<b>Heat Pump or Gas/Electric</b>	universal	yes	yes	yes	yes	yes	yes
<b>Wire Configuration</b>	Home Run	Home Run	4 wire	2 wire twisted pair 2 24V	2 wire twisted pair	Twisted pair	2 wire daisy chain
<b>Damper Configuration</b>	round & rect	round & rect	round, rect, D-Fuser	round & rect	round, rect, D-Fuser	round & rect	existing
<b>Damper Movement</b>	two position	two position	modulating	two position	modulating	modulating & two position	modulating
<b>Damper Capacity</b>	.5"-1.75" S.P.	.5"-1.75" S.P.	1.75" S.P.	.5" S.P.	1.75" S.P.	.5"-1.75" S.P	existing
<b>Number of Cool Stages</b>	1	1 - 5 *	N/A	2	2	1 - 5 *	1 - 5 *
<b>Number of Heat Stages</b>	1 HP w/ aux EM Heat	1 - 4 *	N/A	2	3	2 ***	1 - 4 *
<b>Remote Monitoring Communication Capability</b>	yes	yes **	no	no	no	yes	yes
<b>Thermostat with Remote Sensor Capability</b>	yes	yes	yes	Field Supplied	yes	yes	yes

\* Multi-stage capable when used with CAPL series capacity controls. 5 stages for systems using economizer.

\*\* Remote monitoring available when used with ZonexCommander System.

\*\*\* 3-stage heat with DIGIHP Heat Pump Thermostat (Stand Alone only).